

Industrial cabinet. with 1 Schuko 2P+T 250V
+ 1 2P+E 16A 250V + 1 3P+N+E 16A 400V



Features

Enclosure type	Distribution
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
No.Modules (18 mm)	8
Modules per row	8
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	215x500x160
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Door color	Fume
Battens included	Yes (Screw terminals)
No.of terminals and size	12x6 mm2 + 2x16 mm2
Ticket type	With centricity points .
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw
Door closing system	Handle

Possibility of mounting with key / padlock	Si (no incluido)
Possibility of putting lock	Key
Possibility of mounting DIN rail	Yes (included)
Common applications	Industrial environments (factories, warehouses, etc.)

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE EN	UNE-EN 61439-1: 2021
According to REBT	Yes
According to European Directive 2014/35 / EU.Low voltage directive	Yes