

Industrial panel with 2 sockets 2P+E 230V 16A

Cuadro industrial fabricado según normativa EN 61439-1:2012. Dimensiones 270x250x160 mm.Con protecciones .
Conexiones realizadas con punteras . Incluye declaración de conformidad.y documentación técnica .



Features

Enclosure type	Distribution
Installation method	Surface
Use	Construction site
Location type	Exterior and interior
No.Modules (18 mm)	11
Modules per row	11
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	270x250x160
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Door color	Fume
Battens included	Yes (Screw terminals)
Strip type	Ground
No.of terminals and size	12x6 mm2 + 2x16 mm2
Ticket type	With centricity points .
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw

Door closing system	Handle
Possibility of mounting with key / padlock	No
Possibility of putting lock	Key
Possibility of mounting DIN rail	Yes (included)
Common applications	Industrial wired cabinet

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE EN	UNE-EN 61439-1: 2021
According to REBT	Yes
According to European Directive 2014/35 / EU.Low voltage directive	Yes