

Industrial wired cabinet of 32 modules, 63A.

Industrial wired cabinet INDUBOX. Components: 2 Flush socket 2P+E, 16A. IP54
2 Angled industrial flush socket 3P+E, 32A 400V~. IP44. 2 Angled industrial flush
socket 3P+E, 16A 400V~. IP44. 1 Miniature Circuit Breaker 3P, 32A. Breaking
capacity 6kA. 1 Miniature Circuit Breaker 3P, 16A. Breaking capacity 6kA. 1
Miniature Circuit Breaker 1P+N, 16A. Breaking capacity 6kA. 1 Residual Current
Circuit-Breaker 4P, 63A. 2 modules. Breaking capacity 6kA.



Features

Enclosure type	Distribution
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
No. Modules (18 mm)	32
Modules per row	16
Metallic DIN profile	Yes
Dimensions outside (mm) (width x height x depth)	362x500x160
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Door color	Fume
Battens included	Yes (Screw terminals)
Strip type	Ground
No. of terminals and size	12x6 mm2 + 2x16 mm2
Ticket type	With centricity points.
Sealable	Yes
Linkable	Vertically and horizontally

Lid closure system	Ultra-fast metal screw
Door closing system	Handle
Possibility of mounting strips	Yes (included)
Possibility of mounting with key / padlock	Si (no incluido)
Possibility of putting lock	Key
Possibility of mounting DIN rail	Yes (included)
Common applications	Industrial environments (factories, warehouses, etc.)

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations	UNE-EN 62208: 2012
According to Regulations UNE/EN	UNE-EN 61439-1: 2021 UNE-EN 61439-3: 2012 UNE-EN 61439-4: 2013
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes