

Cable extension with 4 sockets 2P+E,16A 250V~With light switch. 1.5m of cable H05VV-F 3G1,5mm². With surge and overload protector.

Cable extension with 4 sockets 2P+E, 16A 250V~. MAX. 3680W. 850°C GWT. With light switch. 1,5 m cable H05VV-F 3G1,5mm². White colour. With holes for fixing by screws to the wall and orifice por fixing by means of flanges to tubes. With surge and overload protector. Made of Polycarbonate. Serie ION.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Type	Multiple base
No. of bases	4
Basic characteristics	2P+E, 16A 250V~
Surge protection	Yes
Cable length	1,5 m.
Maximum power	3.680 W
Light switch	Yes
Cable	Yes
Cable Features	H05VV-F 3G1,5mm ²
Terminal system	Screw connection
Mini trunking input	Yes, for 7x12, 10x16, 10x20 and 12x12
Possibility of using hanger	Yes
Possibility of using KIT-DIN35	Yes
Wall fixing holes	Yes

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWEPT)	850 °C
Heat resistance (Ball pressure)	125 °C

Ambient operating temperature -5 °C ; +60 °C

Free of halogens Yes

Regulations

CE marking Yes

According to Regulations UNE/EN UNE-20315-1-1:2017; UNE-20315-1-2:2017

According to REBT Yes

According to European Directive 2014/35 / EU. Low voltage directive Yes

Sustainability

According to European Directive 2011/65/UE (RoHS) Yes (Complies with UNE EN 50581)

According to European Directive 2012/19/UE (RAEE2) Yes

Sketch

