

Flush connection box in hollow partition. 300 x 150 x 75 mm.

Flush connection box in hollow partition. 300 x 150 x 75 mm. Cover with screws.  
Fixing system by claws  
Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Enclosure type	Connection and derivation
Installation method	For dry wall
Use	Domestic / Tertiary
Location type	Inside
Dimensions outside (mm) (width x height x depth)	300x150x75
Dimensions inside (mm) (Width x Height x Depth)	295x142x76
Dimensions gap (mm) (Width x Height x Depth)	300x148x77
Case material	Insulation
Case color	Blue
Cap color	White
Ticket type	Unfathomable
Linkable	Vertically and horizontally
Lid closure system	Metal screw
Possibility of mounting DIN rail	Yes (not included)
Fixing system to the hollow partition.	Metal claw
With grommets at the bottom to fix the tubes or cables with cable ties, quantity	Yes
With recessed hole marking system	Yes

Technical data

Fire resistance (GWT)	850°C
Heat resistance (Ball pressure)	70°C
Ambient operating temperature	-5°C ; +60°C
Work stress	400 Vca
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	The Directive 2011/65/EU (RoHS II) is not applicable as it does not correspond to the definition of Electrical and Electronical Equipment (EEE) as per article 3.1
According to European Directive 2012/19/UE (RAEE2)	Not applicable because it does not meet the definition of Electrical and Electronic Equipment (EEE) as described in Article 3.1(a) of Directive 2012/19/EU (WEEE II).