


Watertight connection box 270x250x140 mm. Grey and transparent cover.

Waterproof industrial box. IP65. IK08. External dimensions 270 x 250 x 140 mm. Grey and transparent cover. Smooth side dotted . Stainless steel ultra fast closing screws. Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Connection and derivation
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	270x250x140
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Transparent
Battens included	No
Sealable	Yes
Lid closure system	Ultra-fast metal screw
Possibility of mounting strips	Yes (not included)
Possibility of putting lock	Not
Possibility of mounting DIN rail	Yes (not included)
Valid for photovoltaic installations	Yes

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08

Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022. UNE-EN 60670-22:2007.
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sketch

