

**Connection sealed box without cones. Grey colour.
External dimensions 270x500x140 mm Internal
dimensions 263 x 493 x 129 mm**

Connection sealed box without cones. Grey colour. With centricity points. IP65. IK08. External dimensions 270x500x140 mm Interior dimensions 263 x 493 x 129 mm. Quick closure with stainless screws.

Common applications: Industrial environments (factories, warehouses, etc.)



Features

Enclosure type	Connection and derivation
Installation method	Surface
Use	Industrial
Location type	Exterior and interior
Dimensions outside (mm) (width x height x depth)	270x500x140
Dimensions inside (mm) (Width x Height x Depth)	263x493x129
Case material	Insulation
Case color	Grey (RAL7035)
Cap color	Grey (RAL 7035)
Battens included	No
Ticket type	With centricity points.
Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Ultra-fast metal screw
Possibility of mounting strips	Yes (not included)
Possibility of mounting plate	Yes (not included)
Possibility of mounting DIN rail	Yes (not included)

Valid for photovoltaic installations	Yes
--------------------------------------	-----

Technical data

Protection Degree (IP)	IP65
Protection Degree (IK)	IK08
Impact shock resistance	Strong
Insulation class	Class II
Fire resistance (GWEPT)	650 °C
Heat resistance (Ball pressure)	70 °C
UV resistance	Yes
Free of halogens	Yes
Suitable for saline environments	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60670-1:2022 UNE- EN 60670-22:2007
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sketch

