

## Miniature Circuit Breaker 2P, 25A. Breaking capacity 6kA. C curve.

Miniature Circuit Breaker 2P, 25A. Breaking capacity 6kA. C curve. 2 modules. 240/415V AC (50 - 60 Hz).

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



### Features

Mechanical durability	20.000 cycles
Protection type (modular)	Magnetothermic switch
No. of poles	2P
Modules (18 mm)	2
Network type	Alternating current (ac)
Trigger curve	C
Short circuit capacity	6 kA
Fixation	35mm DIN rail
Connection capacity	Up to 25 mm <sup>2</sup>
Possibility of using pin type combs	Yes
Nominal current	25A
Nominal voltage	230/400 Vca - (50/60 Hz)

### Technical data

Fire resistance (GWT)	960°C
Ambient operating temperature	-5°C -> +40°C
Free of halogens	Yes

## Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE EN 60898-1
According to REBT	Yes
AENOR certificate	Yes
CB certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

## Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes