

2-way switch / Light switch 10AX 250V~. Flush.

2-way switch / Light switch 10AX 250V~. Flush. Graphite colour. Without frame. Quick connection.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

| | |
|------------------------|---------------------------|
| Mechanism type | Switch |
| Type of installation | Flush |
| Pilot light | Yes |
| Rated current | 10AX |
| Nominal voltage | 250V~ (50/60 Hz) |
| Connection type | Fast connection |
| Flexible cable section | Up to 2.5 mm ² |
| Rigid cable section | Up to 2.5 mm ² |
| Type of operation | Rocker key |
| With fixing claws | Yes |

Technical data

| | |
|---------------------------------|----------|
| Protection Degree (IP) | IP40 |
| Fire resistance (GWT) | 850°C |
| Heat resistance (Ball pressure) | 70/125°C |
| Free of halogens | Yes |

Regulations

| | |
|------------|-----|
| CE marking | Yes |
|------------|-----|

| | |
|--|----------------|
| UK marking | Yes |
| CMim marking | Yes |
| According to Regulations UNE/EN | UNE-EN 60669-1 |
| According to REBT | Yes |
| According to European Directive 2014/35 / EU. Low voltage directive | Yes |

Sustainability

| | |
|---|----------------------------------|
| According to European Directive 2011/65/UE (RoHS) | Yes (Complies with UNE EN 50581) |
| According to European Directive 2012/19/UE (RAEE2) | Yes |