

Socket 2P+E, 16A 250V ~ + USB socket 2.1A 5V.

Socket 2P+E, 16A 250V ~ + USB socket 2.1A 5V. Flush. Silver colour. With shutter. Without frame. Quick connection. Dimensions 83x81 mm.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Mechanism type	Fixed base + USB
Type of installation	Flush
Rated current	16A - 2,1A _{dc}
Nominal voltage	250V~ (50/60 Hz) - 5V _{dc}
Connection type	Fast connection
Flexible cable section	Up to 2.5 mm ²
Rigid cable section	Up to 2.5 mm ²
With fixing claws	Yes

Technical data

Protection Degree (IP)	IP40
Fire resistance (GWT)	850°C
Heat resistance (Ball pressure)	70/125°C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-1 ; Reg (UE) 2019/1782

According to REBT	Yes
-------------------	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
--	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
--	----------------------------------

According to European Directive 2012/19/UE (RAEE2)	Yes
---	-----
