

Socket 2P, 16A 250V~. Surface.

Socket 2P, 16A 250V~. Surface. Graphite colour. Inputs for 10x16, 10x20 and 16x16 mm mini-trunking.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Mechanism type	Fixed base
Type of installation	Surface
Rated current	16A
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Mini trunking input	Yes
Dimensions	74 x 72 x 28
Monobloc (with frame included)	Yes
Frame color	Graphite

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWT)	750/850°C
Installation temperature	-5°C -> +60°C
Free of halogens	Yes

Regulations

CE marking	Yes
CMim marking	Yes

According to Regulations UNE/EN	UNE 20315-1-1:2017 UNE 20315-1-2:2017
---------------------------------	--

According to REBT	Yes
-------------------	-----

According to European Directive 2014/35 / EU. Low voltage directive	Yes
--	-----

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
--	----------------------------------

According to European Directive 2012/19/UE (RAEE2)	Yes
---	-----