

Socket 2P+E, 16A 250V~ + Double 2-way switch 10AX 250V~. Surface.

Socket 2P+E, 16A 250V~ + Double 2-way switch 10AX 250V~. Surface. White colour. Dimensions 148 x 72 x 28 mm. Inputs for 10x16, 10x20 and 16x16 mm mini-trunking. Screw connection.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Mechanism type	switch + fixed base
Type of installation	Surface
Rated current	10AX
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Mini trunking input	Yes
Type of operation	Rocker key
Dimensions	148 x 72 x 42
Monobloc (with frame included)	Yes
Key color	White
Frame color	White

Technical data

Protection Degree (IP)	IP20
Fire resistance (GWT)	750/850°C
Installation temperature	-5°C -> +60°C
Free of halogens	Yes

Regulations

CE marking	Yes
------------	-----

UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-1
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes (Complies with UNE EN 50581)
According to European Directive 2012/19/UE (RAEE2)	Yes