



What makes the Green Series so special



The advantages of the Green Series are manifold



Less energy consumption

The new Green Series achieves even higher energy savings of up to 11% (depending on the unit) through renewed unit optimisation and is therefore noticeably more cost-efficient.



Less coolant

The coolant requirement could be reduced by up to 50%. This minimises the use of resources, lowers the Global Warming Potential (GWP) and supports the objectives of the European F-Gases-Regulation.



Future proof

All units of the new Green Series are already certified according to UL 60335 listed. The addition of the word "listed" facilitates certification, as the units do not have to be approved as part of the overall system.



Intelligent commissioning

By using a jumper, a simple change between 400V and 460V is now also possible quickly and easily for the 3-phase units. The connector plug is fully recessed in the now centrally placed connection area.

Further Features

All the advantages that have distinguished our DTI/DTS series so far have of course been retained or even improved. To name just a few:

- Cut-out compatibility of all performance classes with hereditary units and also with other cooling concepts, e.g. with air/water heat exchangers.
- Simple and quick installation in a few minutes in the partially recessed version
- Large distances between air inlet and outlet for particularly good ventilation
- Maximum ease of service due to easy access to the main components
- Increase in protection class from IP54 to IP55 to the cabinet

For every application

Installa-	Perform.	Voltage			Cover material		Controller***	
tion*	class	115V	230V	400/460V	Steel sheet**	stainless steel	SC	MC
DTI / DTS	1000W	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc
	1500W	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc
	2000W	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc
	2500W			\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc
	4000W			\bigcirc	\bigcirc	\bigcirc	\bigcirc	\bigcirc

^{*} DTI - partially recessed mounting, quick installation; DTS - door- or sidemounting

Calculate energy efficiency by yourself



If you would like to get an overview of possible savings potentials of your application, then why not visit our energy efficiency calculator on our homepage.

Simply enter the power, the load and your price per kWh and you will receive a clear presentation of your savings as a pdf file.

www.pfannenberg.com/GreenSeries

Further information

Are you interested in the cooling units of our new Green Series? Would you like more information about our solutions and our portfolio for control cabinet air conditioning? Below you will find two links to help you. We look forward to receiving your feedback



Green Series



Contact form

^{**} Galvanised sheet steel, RAL7035 powdered. Other colours on request.

^{***} SC - Standard-Controller with basic functions; MC - Multi-Controller /w extended features (you can find more details on our website)

Pfannenberg Your global partner for thermal management

- Over 60 years of experience in thermal management, signaling technology and liquid cooling
- · Ability and flexibility to develop tailor-made solutions in cooperation with the customer
- Experience with maintenance and support of projects around the world
- Global presence with several own production sites
- Global service network
- You can find an overview of our international network <u>here</u>.



Pfannenberg Europe GmbH Werner-Witt-Straße 1 21035 Germany pfannenberg.com

Tel.: +49 (040) 734 12 0 Fax: +49 (040) 734 12 101 Email: info@pfannenberg.com

