

2-way switch sealed 10AX 250V~. IP54. Surface.

Sealed 2-way switch 10AX 250V~. IP54. Surface. Tube inputs up to Ø 20 mm. External dimensions 65 x 80 x 55 mm. Screw connection.

Common applications: Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)



Features

Mechanism type	Switch
Type of installation	Surface
Rated current	10AX
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Tube inlet	Up to Ø 20 mm
Flexible cable section	Up to 2.5 mm ²
Rigid cable section	Up to 2.5 mm ²
Type of operation	Rocker key
Dimensions	65 x 80 x 55
Monobloc (with frame included)	Yes
Frame color	Grey

Technical data

Protection Degree (IP)	IP54
Insulation class	Class II
Fire resistance (GWEPT)	650/850 °C
Heat resistance (Ball pressure)	70/125 °C
Installation temperature	-5 °C -> +60 °C

Free of halogens	Yes
------------------	-----

Regulations

CE marking	Yes
According to Regulations UNE/EN	UNE-EN 60669-1:2018
According to REBT	Yes
VDE certificate	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Yes
According to European Directive 2012/19/UE (RAEE2)	Yes
According to Regulations (RoHS)	UNE-EN IEC 63000:2022

Sketch

