

## Sealed 2-way switch lighted.10AX 250V~. IP54. Surface.

Sealed 2-way switch lighted.10AX 250V~. IP54. Surface. Tube inputs up to Ø 20 mm. External dimensions 65 x 80 x 55 mm. Screw connection.

Common applications: Domestic / tertiary outdoor environment (garden, swimming pool, parking, public road, etc.)



### Features

Mechanism type	Switch
Type of installation	Surface
Pilot light	Yes
Rated current	10AX
Nominal voltage	250V~ (50/60 Hz)
Connection type	Screw connection
Tube inlet	Up to Ø 20 mm
Flexible cable section	Up to 2.5 mm <sup>2</sup>
Rigid cable section	Up to 2.5 mm <sup>2</sup>
Type of operation	Rocker key
Dimensions	65 x 80 x 55
Monobloc (with frame included)	Yes
Frame color	Grey

### Technical data

Protection Degree (IP)	IP54
Insulation class	Class II
Fire resistance (GWEPT)	650/850 °C
Heat resistance (Ball pressure)	70/125 °C

Installation temperature -5 °C -> +60 °C

Free of halogens Yes

## Regulations

CE marking Yes

According to Regulations UNE/EN UNE-EN 60669-1:2018

According to REBT Yes

VDE certificate Yes

According to European Directive 2014/35 /  
EU. Low voltage directive Yes

## Sustainability

According to European Directive  
2011/65/UE (RoHS) Yes

According to European Directive  
2012/19/UE (RAEE2) Yes

According to Regulations (RoHS) UNE-EN IEC 63000:2022

## Sketch

