

Flush distribution box of 14 modules. With metallic frame and door, white colour.

Flush distribution box of 14 modules. With metallic frame and door, white colour. Flush dimensions 330 x 297 x 88 mm.

Common applications: Indoor domestic / tertiary environment (Interior of home, offices, shops, etc.)



Features

Enclosure type	Distribution
Installation method	Flush in work
Use	Domestic / Tertiary
Location type	Inside
No. Modules (18 mm)	14
Modules per row	14
Removable frame	Yes
Dimensions inside (mm) (Width x Height x Depth)	330 x 297 x 88
Dimensions gap (mm) (Width x Height x Depth)	330 x 297 x 88
Case material	Insulation
Frame and door material	Metallic stainless
Case color	Gray (RAL7035)
Cap color	White
Door color	White
Door opening	Horizontal
Battens included	Yes (Screw terminals)
Strip type	Ground
No. of terminals and size	13x6 mm ² + 4x16 mm ²
Ticket type	Unfathomable

Sealable	Yes
Linkable	Vertically and horizontally
Lid closure system	Plastic claw
Door closing system	Handle
Reversible door	Yes
Possibility of mounting strips	Yes (included)
Possibility of mounting with key / padlock	Key
Possibility of mounting plate	Key included
Possibility of mounting DIN rail	Yes (included)
Alignment marks	Both
Possibility of mounting .PL-MP28 plate	Yes (not included)
With grommets at the bottom to fix the tubes or cables with cable ties, quantity	Yes
With recessed hole marking system	Yes

Technical data

Protection Degree (IP)	IP40
Protection Degree (IK)	IK07
Insulation class	Class II
Fire resistance (GWT)	650°C
Heat resistance (Ball pressure)	70°C
Installation temperature	-5°C -> +60°C
Work stress	<1000 Vca ; 1500 Vcc
Thermal power dissipated	30 W
UV resistance	Yes
Free of halogens	Yes

Regulations

CE marking	Yes
UK marking	Yes
CMim marking	Yes
According to Regulations UNE/EN	UNE-EN 62208
According to REBT	Yes
According to European Directive 2014/35 / EU. Low voltage directive	Yes

Sustainability

According to European Directive 2011/65/UE (RoHS)	Not applicable
According to European Directive 2012/19/UE (RAEE2)	Yes
